

Speed Queen

COIN-OPERATED WASHER-EXTRACTORS

30 lb. (13 kg) WASHER-EXTRACTOR

40 lb. (18 kg) WASHER-EXTRACTOR



Speed Queen

BUILT BETTER TO LAST LONGER

WASHER-EXTRACTOR SPECIFICATIONS

Meeting Your Needs

Today's coin laundries need laundry equipment that is flexible, reliable, and delivers excellent cleanability every time. Speed Queen's washer-extractor does just that. We've developed units that will fulfill your basic needs and exceed your expectations.

CLEANABILITY Linens last longer when they receive the right care. Our washer-extractors combine cycle flexibility with adjustable cycle times, which can be set as short as 16.5 minutes or as long as 27.5 minutes. Our factory preset cycle is 21.5 minutes to provide superior washability and fast customer turnover.

RELIABILITY At Speed Queen we're confident that our washer-extractors are built better to last longer, so we are offering a three-year limited warranty* to prove it.

*Parts only. Labor not included. See Speed Queen Warranty Bond for specifics.

	SC30	SC40
Dry Weight Capacity	30 lb. (13 kg)	40 lb. (18 kg)
Cylinder Diameter	24" (610 mm)	26.25" (667 mm)
Cylinder Volume	4.19 cu. ft. (118 liters)	6.34 cu. ft. (180 liters)
Width (in/mm)	29" (737 mm)	30.62" (778 mm)
Depth (in/mm)	35" (889 mm)	40.25" (1022 mm)
Height (in/mm)	45" (1143 mm)	47.25" (1200 mm)
Wash Speed	47 RPM	47 RPM
Extract Speed	480 RPM	470 RPM
Extract G-Force	78	82
Door Opening Size (in/mm)	14.34" (364 mm)	16.25" (413 mm)
Door Bottom To Floor (in/mm)	14" (356 mm)	14.5" (368 mm)
Drain Diameter (in/mm)	2" (52 mm)	3" (76 mm)
Drain Height To Floor (in/mm)	4" (102 mm)	4.08" (104 mm)
Electrical Specifications		
Circuit Breaker Requirements and Full Load Amperages* (Circuit•Full Load Amps)	208-240/60/1/20•10 amp 208-240/60/3/15•7 amp 380-415/50/3/15•4 amp	208-240/60/1/25•12 amp 208-240/60/3/20•7 amp 440-480/60/3/15•5 amp 380-415/50/3/15•5 amp
Net Weight	495 lb. (225 kg)	650 lb. (295 kg)
Standard Shipping Weight	535 lb. (243 kg)	680 lb. (309 kg)
Wood Crate Shipping Weight	601 lb. (273 kg)	760 lb. (345 kg)
Shipping Dimensions Approx. - Inches (mm)	Height x Width x Depth 53.5" x 30.5" x 37.5" (1359 x 775 x 953)	Height x Width x Depth 56" x 32" x 41" (1422 x 813 x 1041)
Agency Approvals**	ETL, ETLc, CE	ETL, ETLc, CE

* Standard domestic voltage 208-240/60/3. Circuit breaker and amp draw data shown is for standard voltage models without auxiliary heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

** Agency approvals may vary depending on configuration. Consult factory for details. Steam connection requires 1/2" N.P.T. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification.



www.speedqueen.com

Alliance Laundry Systems
Shepard Street, Ripon, WI 54971 Telephone: 1-800-345-5649

