

Speed Queen

COIN & CARD-OPERATED

Drying Tumblers

25 lb (11.34 kg) Slim Line

30 lb (13.6 kg) Slim Line

30 lb (13.6 kg) Stack Tumbler

35 lb (15.88 kg) STANDARD



Speed Queen®

BUILT BETTER TO LAST LONGER

LET SPEED QUEEN LEAD THE WAY...

As America's largest commercial laundry equipment manufacturer, Speed Queen stands for innovation. As a leader in laundry technology, our electronically controlled laundry units for coin and card operation will provide you with quality, efficiency, convenience, and flexibility well into the 21st century. Since 1908 we have been committed to our tradition of quality products, backed by superior customer service.

NetMaster™ System

Speed Queen's NetMaster™ System of technologically advanced laundry products offer more flexibility and accountability benefits than you ever thought possible. Now you can program vend prices, cycle times, rinse options, and cycle selections while auditing machine operation simply by touching a series of control pads.



There are three options available to program your machines, manual, Micro-Wand III™ and network with NetMaster™ models. What ever your needs, Speed Queen has the right option for you. It's almost like having a tumbler built to your specifications. Your customers will be amazed at how easy and convenient it is to launder garments. Satisfied customers translate into profits for you.

CardMate™ Plus System

Speed Queen introduces a revolution in laundry room convenience, accountability and profitability.

The CardMate™ Plus System offers the industry's first full line of commercial washers and

dryers with factory-installed, smart card reader controls on individual laundry units for cashless operation.

Both you and your customers will benefit from the convenience of CardMate™ Plus.




Drying Tumblers



Concentrated Airflow

Our concentrated airflow pattern and sealed cylinder rims, available on slimline and stack tumblers, ensure that every bit of warm air enters the cylinder and passes through the clothes. Therefore, fabrics receive the most concentrated drying possible and no energy is wasted.



Large, Easy to Clean Lint Compartment

Maintaining maximum airflow promotes drying efficiency and is essential for a successful coin laundry. Speed



Queen's fine mesh lint screen cleans itself automatically by depositing lint into a large storage area (single tumbler pictured) for easy removal. It allows customers to receive the most efficient drying while eliminating the need to manually clean filter after each use. The stack's unique lint drawers, for each cylinder, offers maximum lint capacity in a minimum amount of space.

Durable Stainless Steel Door

Continuous opening and closing can take a toll on tumbler doors in a busy coin laundry. Speed



Queen's attractive stainless steel door will not chip and incorporates a durable latch to secure the door throughout the cycle, preventing unwanted door openings. Extra-wide hinges evenly distribute forces on the door so it stands up to heavy usage.

Simplicity and Compatibility

Fewer moving parts mean fewer maintenance problems and less wear. Because each component is designed to perform a singular task, none is overworked. The result is less wear individually and increased

reliability overall. And, to keep things simple, we've designed our slimline and stack tumblers to be compatible for easy installation and repair. In fact, even our control box, which swings out for easy maintenance and accessibility, can be interchanged between different models.




Superior Fit and Finish

We've designed our stack and slimline tumblers for efficient use of space and maximum customer potential. At 42.875" (1089 mm), our stack tumblers have the shallowest install size in the industry; the slimline's narrow 28" (711 mm) width allows the installation of more tumblers in a given space. Speed Queen's tumblers not only fit well together—they have an attractive design.

Our innovative paint system electrostatically applies paint for superior bonding and corrosion resistance. The paint is baked on the equipment inside and out to provide a tough and durable finish.

Control Options



Fully programmable NetMaster™ control



Fully programmable electronic control (EDC)

Our advanced NetMaster™ and Electronic DISPLAY Control™ (EDC) panel make it easy for customers to locate vend price, cycle times, and cycle selections.

Customers will appreciate knowing the status of their laundry and the ability to be more efficient with their time.


Activation Options



Single Coin Drop



Dual Coin Drop



Card Reader



Quarter-Turn Coin Meter

Speed Queen lets you customize your activation options. Our new single coin drop is now available on our complete line of equipment.

Its all-metal design reduces coin jamming and provides superior coin validation. Dual coin drop for International use and a USA dual coin conversion are also available.

Our new CardMate™ Plus System offers the convenience and safety of cashless operation.

3 YEAR WARRANTY

At Speed Queen, we're confident that our drying tumblers are built better to last longer and we're offering the following limited warranty to prove it:

Through three years*

Free replacement for any part of the drying tumbler which fails as a result of a defect in material or workmanship after the date of original installation.

*Parts only, labor not included.
See Speed Queen Warranty Bond for specifics.

Drying Tumbler Specifications

	25 lb	30 lb	30 lb Stack	35 lb
Width (in/mm)	28" (711 mm)	28" (711 mm)	31 1/2" (800 mm)	31 1/2" (800 mm)
Depth (in/mm)	38 7/8" (987 mm)	44 7/8" (1140 mm)	42 7/8" (1089 mm)	44 7/8" (1140 mm)
Height (in/mm)	63 7/8" (1622 mm)*	63 7/8" (1622 mm)*	76 1/4" (1937 mm)	63 7/8" (1622 mm)*
Cylinder Depth	24" (610 mm)	30" (762 mm)	26" (660 mm)	30" (762 mm)
Cylinder Diameter	26 1/2" (673 mm)	26 1/2" (673 mm)	30" (762 mm)	30" (762 mm)
Cylinder Volume	7.66 cu. ft. (217 liters)	9.57 cu. ft. (271 liters)	10.63 cu. ft. (301 liters)	12.27 cu. ft. (347 liters)
Dry Capacity Filling Ratios	25 lb (11.3 kg) (20:1 = 10.9 kg) (25:1 = 8.7 kg)	30 lb (13.6 kg) (20:1 = 13.6 kg) (25:1 = 10.8 kg)	2 x 30 lb (13.6 kg) (20:1 = 15.1 kg) (25:1 = 12.0 kg)	35 lb (15.9 kg) (20:1 = 17.4 kg) (25:1 = 13.9 kg)
Airflow	60 Hz: 450 CFM (212 liters/sec.) 50 Hz: 410 CFM (194 liters/sec.)	60 Hz: 450 CFM (212 liters/sec.) 50 Hz: 410 CFM (194 liters/sec.)	60 Hz: 350 CFM (165 liters/sec.) 50 Hz: 320 CFM (151 liters/sec.)	60 Hz: 520 CFM (245 liters/sec.) 50 Hz: 470 CFM (222 liters/sec.)
Energy Data	Gas Models 64,000 Btu/hr (18.8 kW) Steam Models At 80 psig (5.5 bar): 3.0 BHP, 100,000 Btu/hr (29.4 kW) At 15 psig (1.0 bar): 2.1 BHP, 71,400 Btu/hr (20.9 kW) Electric Models 12 kW	Gas Models 73,000 Btu/hr (21.4 kW) Steam Models At 80 psig (5.5 bar): 3.0 BHP, 100,000 Btu/hr (29.4 kW) At 15 psig (1.0 bar): 2.1 BHP, 71,400 Btu/hr (20.9 kW) Electric Models 21.0 kW	Gas Models 146,000 Btu/hr (42.8 kW) total 73,000 Btu/hr (21.4 kW) per pocket Steam Models At 80 psig (5.5 bar): 2.3 BHP, 78,000 Btu/hr (22.8 kW) At 15 psig (1.0 bar): 1.6 BHP, 55,700 Btu/hr (16.3 kW) Electric Models 21.0 kW	Gas Models 90,000 Btu/hr (26.4 kW) Steam Models At 80 psig (5.5 bar): 3.4 BHP, 113,500 Btu/hr (33.2 kW) At 15 psig (1.0 bar): 2.4 BHP, 80,300 Btu/hr (23.5 kW) Electric Models 24.0 kW
Electrical Specifications	Gas and Steam Models 120/208-240/60/1; 2W/3W+G 100/200/60/1; 2W+G 100/200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/240/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460-480/60/3; 3W+G Electric Models 208/60/1; 3W+G 240/60/1; 3W+G 200/60/1; 2W+G 200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 240/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G	Gas and Steam Models 120/208-240/60/1; 2W/3W+G 100/200/60/1; 2W+G 100/200/50/1; 2W + G 230-240/50/1; 2W+G 200-208/240/60/3; 3W +G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460 - 480/60/3; 3W+G Electric Models 208/60/1; 3W+G 240/60/1; 3W+G 200/60/1; 2W+G 200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 240/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G	Gas and Steam Models 120/208-240/60/1; 2W/3W+G 100/200/60/1; 2W+G 100/200/50/1; 2W + G 230-240/50/1; 2W+G 200-208/240/60/3; 3W +G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460-480/60/3; 3W+G Electric Models 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G** 240/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G	Gas and Steam Models 120/208-240/60/1; 2W/3W+G 100/200/60/1; 2W+G 100/200/50/1; 2W + G 230-240/50/1; 2W+G 200-208/240/60/3; 3W +G 200/50/3; 3W+G 230-240/50/3; 3W+G 380/400-415/50/3; 3W+G 460-480/60/3; 3W+G Electric Models 208/60/1; 3W+G 240/60/1; 3W+G 200/60/1; 2W+G 200/50/1; 2W+G 230-240/50/1; 2W+G 200-208/60/3; 3W+G 200/50/3; 3W+G 230-240/50/3; 3W+G 240/60/3; 3W+G 380/50/3; 3W+G 400-415/50/3; 3W+G 460-480/60/3; 3W+G
Plumbing Connections	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT One manifold gas connection Steam Models: 3/4" - NPT	Gas Models: 1/2" - NPT Steam Models: 3/4" - NPT
Net Weight	299 lb (135 kg)	331 lb (150 kg)	544 lb (247 kg)	361 lb (164 kg)
Shipping Weight	332 lb (151 kg)	364 lb (165 kg)	582 lb (264 kg)	394 lb (179 kg)
Shipping Dimensions (in/mm)	Width: 30" (762 mm) Depth: 41" (1041 mm) Height: 69" (1753 mm)	Width: 30" (762 mm) Depth: 41" (1194 mm) Height: 69" (1753 mm)	Width: 33 1/2" (851 mm) Depth: 47" (1194 mm) Height: 81" (2057 mm)	Width: 33 1/2" (851 mm) Depth: 47" (1194 mm) Height: 69" (1753 mm)

Tumbler models are made to suit a variety of electrical service characteristics. See your Speed Queen distributor for specifications. Door opening - 22.68" (576 mm). Motor size: fan - 1/4 HP (187W); cylinder - 1/4 HP (187W). Air outlet diameter on 25lb/30lb - 6" (152 mm); 30lb stack/35lb - 8" (203 mm) with one manifold vent connection on 30lb stack. For further details on installation refer to Installation, Operation and Maintenance instructions supplied with the tumbler. Due to continuous product improvements, design and specifications subject to change without notice. Features and certifications may vary by model. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification. Amperage ratings available in Installation Manual.

* Also available in optional heights of 72 1/4" (1835 mm) and 76 1/4" (1937 mm). Also complies with international electrical emissions and immunity standards.

** Not available in EU



www.speedqueen.com



Speed Queen
Alliance Laundry Systems